

									H	D	
		Min.		H	H	R T I			V	4	C
		Thk	Flame	W	A	Elec	Mech		T	9	T
Material Dsg	Color	mm	Class	I	I		Imp	Str	R	5	I
<b>Polyamide 6 (PA6), "DOMAMID" or "AQUAMID", furnished as pellets.</b>											
<b>6 AF (d)</b>	ALL	0.75	V-2	-	-	65	65	65	-	-	0
		1.5	V-2	-	-	65	65	65			
		3.0	V-2	-	-	65	65	65			
<b>6 G (b) V0EF (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>6 G10 V0EF (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>6 G35 V0EF (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>6AFIE (d)</b>	ALL	0.4	V-2	4	2	65	65	65	-	-	-
		0.75	V-2	4	2	120	65	90			
		1.0	V-2	4	2	120	65	90			
		1.8	V-2	4	1	120	65	90			
		3.0	V-2	4	1	120	65	90			
		3.2	V-2	2	0	120	65	90			
<b>6AFIE (d)(f1)</b>	NC, BK	0.8	V-2	4	2	120	65	90	-	-	-
		1.0	V-2	4	2	120	65	90			
		1.8	V-2	4	1	120	65	90			
		3.0	V-2	4	1	120	65	90			
		3.2	V-2	2	0	120	65	90			
<b>6FC (d), 6AV (d), 6AV1 (d), 6S (d)</b>											
	ALL	0.80	V-2	-	-	65	65	65	-	-	-
<b>6G(a)H</b>	ALL	0.75	-	4	0	130	80	125	0	6	0
		1.5	HB	3	0	130	85	130			
		3.0	HB	3	0	130	90	130			

<b>6G20GT96MLS</b>	ALL	0.8	V-2	-	-	65	65	65	-	-	-
		1.0	V-2	-	-	65	65	65			
		3.0	V-2	-	-	65	65	65			
<b>6G35H</b>	ALL	0.75	-	3	0	130	105	125	0	6	0
		1.5	HB	2	0	130	115	130			
		3.0	HB	2	0	130	115	130			
<b>6STC2</b>	NC	0.8	HB	4	0	65	65	65	-	-	-
		3.2	HB	3	0	65	65	65			
<b>6V0M (d)</b>	ALL	1.5	V-0	-	-	65	65	65	-	-	-
<b>6VOM1 (d)</b>	ALL	0.8	V-0	-	-	65	65	65	-	-	-
		3.2	V-0	-	-	65	65	65			
<b>Polyamide 6 (PA6), furnished as pellets.</b>											
<b>6FRMV0</b>	ALL	0.75	V-0	4	0	65	65	65	0	5	0
		1.5	V-0	3	0	65	65	65			
		3.0	V-0	3	0	65	65	65			
<b>6G(b)FRMV2</b>	ALL	0.75	V-2	2	0	115	65	105	0	5	0
		1.5	V-2	2	0	115	65	105			
		3.0	V-2	1	0	115	65	105			
<b>6G20FRMV2</b>	ALL	0.8	V-2	2	0	120	65	105	0	5	0
		1.5	V-2	1	0	120	65	105			
		3.0	V-2	0	0	120	65	105			
<b>6G30FREVO</b>	ALL	0.8	V-0	3	0	130	100	115	0	5	0
		1.6	V-0	3	0	130	105	120			
		3.0	V-0	0	0	130	105	120			
<b>6G30FRMV2</b>	ALL	0.75	V-2	2	0	115	65	105	0	5	0
		1.5	V-2	2	0	115	65	110			
		3.0	V-2	1	0	115	65	110			
<b>Polyamide 66 (PA66), "DOMAMID", furnished as pellets.</b>											
<b>66 G12ST1X H2</b>	ALL	0.8	-	-	-	65	65	65	-	-	-
<b>Polyamide 66 (PA66), "DOMAMID" or "AQUAMID", furnished as pellets.</b>											

<b>66 G(b) V0EF (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>66 G10 V0EF (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>66 G35 V0EF (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>66G(a)H</b>	ALL	0.75	-	4	0	110	90	115	1	6	0
		1.5	HB	4	0	110	100	120			
		3.0	HB	3	0	110	100	125			
<b>66G12ST1X</b>	NC, BK	0.8	HB	-	-	65	65	65	-	-	-
<b>66G20V0AH (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>66G25FC</b>	ALL	0.8	HB	-	-	65	65	65	-	-	-
		1.5	HB	-	-	65	65	65			
		3.0	HB	-	-	65	65	65			
<b>66G25V0AH (d)</b>	ALL	0.75	V-0	-	-	65	65	65	-	-	-
<b>66G25V0P (d)</b>	NC, BK	0.75	V-0	-	-	130	65	65	-	-	-
<b>66G25V0P 1001A</b>	NC, BK	0.8	V-0	-	-	65	65	65	-	-	-
		3.0	V-0	-	-	65	65	65			
<b>66G35H</b>	ALL	0.75	-	4	0	110	105	120	1	6	0
		1.5	HB	3	0	110	115	125			
		3.0	HB	3	0	110	115	125			
<b>66G35V0P (d)</b>	NC, BK	0.75	V-0	-	-	65	65	65	-	-	-
<b>66G40H</b>	NC	0.75	HB	-	-	65	65	65	-	-	-
<b>66SN (d)</b>	ALL	0.80	V-2	-	-	65	65	65	-	-	-
<b>66V0A (d)</b>	ALL	0.8	V-0	-	-	65	65	65	-	-	-
		3.0	V-0	-	-	65	65	65			
<b>Polyamide 66 (PA66), furnished as pellets.</b>											
<b>6/66FRMV0</b>	ALL	0.75	V-0	4	0	65	65	65	0	5	0
		1.5	V-0	3	0	65	65	65			

		3.0	V-0	2	0	65	65	65			
<b>66G25FRPV0 1001</b>	NC, BK	0.8	V-0	2	0	120	105	120	2	5	1
		1.5	V-0	1	0	120	105	120			
		3.0	V-0	1	0	120	115	130			
<b>66G25FRPV0 1003</b>	NC, RD, BK	0.8	HB	1	0	65	65	65	1	5	0
		1.5	V-0	1	0	65	65	65			
		3.0	V-0	0	0	65	65	65			
<b>66G30FREVO</b>	ALL	0.4	V-0	-	-	140	65	65	2	5	0
		0.8	V-0	0	0	140	105	110			
		3.0	V-0	0	0	140	105	110			
<b>66G30FRJVO</b>	ALL	0.40	V-0	0	0	140	65	65	0	5	0
		0.80	V-0	0	0	140	65	65			
		1.5	V-0, 5VA	0	0	140	65	65			
		2.0	V-0, 5VA	0	0	140	65	65			
		3.0	V-0, 5VA	0	0	140	65	65			
<b>Polyamide 66/6 (PA66/6), "DOMAMID" or "AQUAMID", furnished as pellets.</b>											
<b>66/6 V0M (d)</b>	ALL	0.40- 0.44	V-0	-	-	130	90	100	-	-	-
	NC, WT, RD	0.40	V-0	-	-	130	90	100			
		0.75	V-0	-	-	130	90	100			
		1.5	V-0	-	-	130	90	100			
		3.0	V-0	-	-	130	90	100			

(a) - indicates one or two digit number from 6 to 34 denoting glass content

(b) - indicates a two digit number indicating the glass fiber content from 11 to 34 percent

(d) - optional alphanumeric code (2 to 8 digits/letter) denoting color

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Marking: Company name and material designation on container, wrapper or finished part.

[Last Updated](#) on 2015-09-04

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".

